



SwimClear™

Multi-Element Cartridge Filters

CRYSTAL CLEAR WATER,
SUPER DURABLE DESIGN



EXPERT LINE®



ONLY FROM POOL PROS



3+ YEAR PARTS & LABOR WARRANTIES*

*When sold by a Totally Hayward® Partner. Exclusions, other terms and conditions may apply — visit hayward.com/expert for details.

MAXIMUM FLOW WITH MINIMAL MAINTENANCE.

Featuring an assembly of reusable polyester cartridge elements with precision-engineered cores, SwimClear Multi-Element Cartridge Filters provide heavy-duty dirt-holding capacity and extra-long filter cycles. SwimClear filters' top manifold configuration boasts industry-leading hydraulic performance, facilitating maximum flow through all cartridge elements for superior water clarity and increased energy savings.

Reinforced co-polymer tank is durable enough to withstand tough environmental conditions

Low-profile tank base makes removal of cartridge elements fast and simple



Heavy-duty, tamper-proof, one-piece clamp provides quick access to internal components without disturbing plumbing connections

CPVC 2" or 2-1/2" union connections provide maximum hydraulic performance with 2" plumbing

SPECIFICATIONS

Filter Type	Cartridge elements: 225, 325, 425, and 600 ft² [4 cartridge elements]
Filter Tank	High-strength, injection-molded durable glass reinforced copolymer
Filter Element	Reinforced polyester
Performance Range	84 to 150 GPM, 318 to 568 LPM
Dimensions	C2030 – 24" W x 32½" H (58 cm x 81 cm) C3030 – 24" W x 34½" H (58 cm x 87 cm) C4030 – 24" W x 40½" H (58 cm x 102 cm) C6060 – 24" W x 46½" H (58 cm x 117 cm)

FILTER PERFORMANCE DATA

MODEL NUMBER	EFFECTIVE FILTRATION AREA	DESIGN FLOW RATE†	TURNOVER		CLEARANCE FOR HEAD REMOVAL	CARTON WEIGHT
			8 HOURS	10 HOURS		
C2030	225 ft² / 20.9 m²	84 GPM† / 318 LPM	40,320 gal / 153 kl	50,400 gal / 191 kl	15"	50 lbs.
C3030	325 ft² / 30.2 m²	122 GPM† / 462 LPM	58,560 gal / 222 kl	73,200 gal / 277 kl	16"	60 lbs.
C4030	425 ft² / 39.5 m²	150 GPM** / 568 LPM	72,000 gal / 273 kl	90,000 gal / 341 kl	18"	69 lbs.
C6060	600 ft² / 48.8 m²	150 GPM** / 568 LPM	72,000 gal / 273 kl	90,000 gal / 341 kl	22"	79 lbs.

†Based on NSF recommended rate for commercial use at .375 GPM/ft²
**Determined by pump size and piping system hydraulics; 2" piping is recommended for flow rates equal to or greater than 90 GPM (341 LPM).
Hayward doesn't recommend flow rates above 150 GPM.

*When sold by a Totally Hayward® partner. Exclusions, other terms and conditions may apply — visit hayward.com/expert for details.

» hayward.com » 1-888-HAYWARD

SwimClear Filters are listed by: 

Pumps » Filters » Heating » Cleaners » Sanitization » Automation » Lighting » Water Features » White Goods